




RODEO DRIVE



CONSTRUCTION	LOOP
PILE FIBER COMPOSITION	100% Nylon (Polyamide 6)
YARN TYPE	BCF
DYE METHOD	Solution Dyed
PILE WEIGHT	650 g/m ²
NUMBER OF TUFTS	218040/m ²
TUFTING GAUGE	1/12"
PRIMARY BACKING	Non-Woven
SECONDARY BACKING	StableShield - 100% Vinyl
TILE SIZE	25 cm x 100 cm
PILE HEIGHT	3.5 mm / 5.5 mm
TOTAL PILE HEIGHT	8.5 mm
PILE TREATMENT	INVISTA Anti-Soil Treatment, Anti-Microbial (Optional)
RECOMMENDED INSTALLATION	Quarter Turn, Herringbone, Ashlar, Semi Ashlar or Random Plank

SPECIFICATIONS

COLOURLINE



Rodeo Drive 645



Rodeo Drive 647



Rodeo Drive 649



Rodeo Drive 658



Rodeo Drive 673



Rodeo Drive 675



Rodeo Drive 676



Rodeo Drive 677



Rodeo Drive 6645



Rodeo Drive 6647



Rodeo Drive 6649



Rodeo Drive 6658



Rodeo Drive 6673



Rodeo Drive 6675



Rodeo Drive 6676



Rodeo Drive 6677









HOW TO INSTALL


QUARTER TURN




HERRINGBONE




ASHLAR



SEMI ASHLAR



RANDOM PLANK





Standard
CARPETS

www.standardcarpets.com