



VERSA™

DESIGNED SURFACES

Since 1950

VERSA ||

Type 1

Fabric Backed Vinyl Wallcovering



Introducing the new Versa 15 Collection with signature and classic textures and several new exciting patterns, designed by the award winning Versa studio. These 15 oz. wallcoverings are produced in LSI's state-of-the-art facility in Suzhou, China, and are designed and manufactured to strict USA standards. With more than 60 years of experience and distribution around the world, Versa is a trusted resource for achieving your design vision.



15 OZ COLLECTION

Volume

2



Kaisa



Acadia



Panama Linen



Beacon Hill



Omni Linen



Ravelle



Sonoma



Bellagio

Kaisa



Specifications

- Width – 52/54 in (132/137 cm)
- Backing – Osnaburg
- Installation – Reverse hang / Random Match
- Weight – 15 OZ/LY (340 gr/m²)
- Hanging Instructions – [download](#)
- Warranty – [download](#)
- Packing: 30 LY(37.4 m²) / Roll

Environmental Attributes

- Low VOC meets CA01350
- Meets LEED criteria for EQc2
- Meets NSF/ANSI 342 certification; check with distributor for actual level
- Meets GB18585-2001

Fire Resistance Attributes

- USA ASTM E84 Class A
- China GB8624 Class B1
- European EN13501 Class B1
- British BS 476 Part 6 & Part 7 Class 0



燃烧性能等级标识





V15-201



V15-202



V15-203



V15-204



V15-205



V15-206



V15-207

Acadia



Specifications

- Width – 52/54 in (132/137 cm)
- Backing – Osnaburg
- Installation – Reverse hang / Random Match
- Weight – 15 OZ/LY (340 gr/m²)
- Hanging Instructions – [download](#)
- Warranty – [download](#)
- Paking: 30 LY(37.4 m²) / Roll

Environmental Attributes

- Low VOC meets CA01350
- Meets LEED criteria for EQc2
- Meets NSF/ANSI 342 certification; check with distributor for actual level
- Meets GB18585-2001

Fire Resistance Attributes

- USA ASTM E84 Class A
- China GB8624 Class B1
- European EN13501 Class B1
- British BS 476 Part 6 & Part 7 Class 0



燃烧性能等级标识





V15-208



V15-209



V15-210



V15-211



V15-112



V15-213

Panama Linen



Specifications

- Width – 52/54 in (132/137 cm)
- Backing – Osnaburg
- Installation – Straight Hang / Random Match
- Weight – 15 OZ/LY (340 gr/m²)
- Hanging Instructions – [download](#)
- Warranty – [download](#)
- Packing: 30 LY(37.4 m²) / Roll

Environmental Attributes

- Low VOC meets CA01350
- Meets LEED criteria for EQc2
- Meets NSF/ANSI 342 certification; check with distributor for actual level
- Meets GB18585-2001

Fire Resistance Attributes

- USA ASTM E84 Class A
- China GB8624 Class B1
- European EN13501 Class B1
- British BS 476 Part 6 & Part 7 Class 0



燃烧性能等级标识





V15-214



V15-215



V15-216



V15-217



V15-218



V15-219

Beacon Hill



Specifications

- Width – 52/54 in (132/137 cm)
- Backing – Osnaburg
- Installation – Reverse hang / Random Match
- Weight – 15 OZ/LY (340 gr/m²)
- Hanging Instructions – [download](#)
- Warranty – [download](#)
- Packing: 30 LY(37.4 m²) / Roll

Environmental Attributes

- Low VOC meets CA01350
- Meets LEED criteria for EQc2
- Meets NSF/ANSI 342 certification; check with distributor for actual level
- Meets GB18585-2001

Fire Resistance Attributes

- USA ASTM E84 Class A
- China GB8624 Class B1
- European EN13501 Class B1
- British BS 476 Part 6 & Part 7 Class 0



燃烧性能等级标识





V15-220



V15-221



V15-222



V15-223



V15-224



V15-225



V15-226

Omni Linen



Specifications

- Width – 52/54 in (132/137 cm)
- Backing – Osnaburg
- Installation – Straight Hang/ Random Match
- Weight – 15 OZ/LY (340 gr/m²)
- Hanging Instructions – [download](#)
- Warranty – [download](#)
- Packing: 30 LY(37.4 m²) / Roll

Environmental Attributes

- Low VOC meets CA01350
- Meets LEED criteria for EQc2
- Meets NSF/ANSI 342 certification; check with distributor for actual level
- Meets GB18585-2001

Fire Resistance Attributes

- USA ASTM E84 Class A
- China GB8624 Class B1
- European EN13501 Class B1
- British BS 476 Part 6 & Part 7 Class 0



燃烧性能等级标识





V15-227



V15-228



V15-229



V15-230



V15-231



V15-232

Ravelle



Specifications

- Width – 52/54 in (132/137 cm)
- Backing – Osnaburg
- Installation – Reverse hang / Random Match
- Weight – 15 OZ/LY (340 gr/m²)
- Hanging Instructions – [download](#)
- Warranty – [download](#)
- Packing: 30 LY(37.4 m²) / Roll

Environmental Attributes

- Low VOC meets CA01350
- Meets LEED criteria for EQc2
- Meets NSF/ANSI 342 certification; check with distributor for actual level
- Meets GB18585-2001

Fire Resistance Attributes

- USA ASTM E84 Class A
- China GB8624 Class B1
- European EN13501 Class B1
- British BS 476 Part 6 & Part 7 Class 0



燃烧性能等级标识





V15-233



V15-234



V15-235



V15-236



V15-237



V15-238

Sonoma



Specifications

- Width – 52/54 in (132/137 cm)
- Backing – Osnaburg
- Installation – Reverse hang / Radom Match
- Weight – 15 OZ/LY (340 gr/m²)
- Hanging Instructions – [download](#)
- Warranty – [download](#)
- Packing: 30 LY(37.4 m²) / Roll

Environmental Attributes

- Low VOC meets CA01350
- Meets LEED criteria for EQc2
- Meets NSF/ANSI 342 certification; check with distributor for actual level
- Meets GB18585-2001

Fire Resistance Attributes

- USA ASTM E84 Class A
- China GB8624 Class B1
- European EN13501 Class B1
- British BS 476 Part 6 & Part 7 Class 0



燃烧性能等级标识





V15-239



V15-240



V15-241



V15-242



V15-243



V15-244

Bellagio



Specifications

- Width – 52/54 in (132/137 cm)
- Backing – Osnaburg
- Installation – Reverse hang / Random Match
- Weight – 15 OZ/LY (340 gr/m²)
- Hanging Instructions – [download](#)
- Warranty – [download](#)
- Packing: 30 LY(37.4 m²) / Roll

Environmental Attributes

- Low VOC meets CA01350
- Meets LEED criteria for EQc2
- Meets NSF/ANSI 342 certification; check with distributor for actual level
- Meets GB18585-2001

Fire Resistance Attributes

- USA ASTM E84 Class A
- China GB8624 Class B1
- European EN13501 Class B1
- British BS 476 Part 6 & Part 7 Class 0



燃烧性能等级标识





V15-245



V15-246



V15-247




V15-248



V15-249



V15-250



Pattern Name	Pattern Number	Weight	Backing	Installation	Roll Size
Kalca	V15-201-V15-207	15oz (340 gr/m)	Osnaburg	Reverse Hang/Random Match	52" x 54" x 30 Yards
Acadia	V15-208-V15-213	15oz (340 gr/m)	Osnaburg	Straight Hang/Random Match	52" x 54" x 30 Yards
Panama Linen	V15-214-V15-219	15oz (340 gr/m)	Osnaburg	Straight Hang/Random Match	52" x 54" x 30 Yards
Beacon Hill	V15-220-V15-226	15oz (340 gr/m)	Osnaburg	Reverse Hang/Random Match	52" x 54" x 30 Yards
Omni Linen	V15-227-V15-232	15oz (340 gr/m)	Osnaburg	Straight Hang/Random Match	52" x 54" x 30 Yards
Avella	V15-233-V15-238	15oz (340 gr/m)	Osnaburg	Reverse Hang/Random Match	52" x 54" x 30 Yards
Sonoma	V15-239-V15-244	15oz (340 gr/m)	Osnaburg	Reverse Hang/Straight Across Match	52" x 54" x 30 Yards
Belagio	V15-245-V15-250	15oz (340 gr/m)	Osnaburg	Reverse Hang/Random Match	52" x 54" x 30 Yards

Specifications

- 52-54" (132/137 cm) width
- High tear and tensile strength
- Highly cleanable & stain resistant
- Color fast water-based inks
- Standard Non-ortho phthalate plasticizers
- No formaldehyde or heavy metals

Visit versa.covering.com for technical information.

- Meets /Exceeds CCC-W-408D & W101 Specifications
- Meets BS476 Part 6/7-British Class 0
- Fire Certification - Class A - ASTM E84
- Low VOC CAD1350 (Indoor Air Quality)
- Meets BS476 Part 6/7-British Class 0
- Fire Certification-GB6624-2013-81(B-e2,d0,r0)

Warranty

Versa products are guaranteed to be free of defects in workmanship and materials for five years.

For additional colors and patterns, please visit versa.covering.com
All trademarks are the property of their respective owners.

Volume
2

15 OZ : TYPE I
WALLCOVERING



LSI
WALLCOVERING