



DOMAIN




CONSTRUCTION	VLOC
PILE FIBER COMPOSITION	100% Nylon (Polyamide 6)
YARN TYPE	BCF
DYE METHOD	Solution Dyed
PILE WEIGHT	750 g/m ²
NUMBER OF TUFTS	232260/m ²
TUFTING GAUGE	1/12"
PRIMARY BACKING	Non-Woven
SECONDARY BACKING	StableShield - 100% Vinyl
OPTIONAL BACKING	Recova -PU Cushion, EcoShield -100% Recycled Vinyl
TILE SIZE	50 cm x 50 cm
PILE HEIGHT	3.5 mm / 5.0 mm
TOTAL PILE HEIGHT	7.0 mm
PILE TREATMENT	INVISTA Anti-Soil Treatment, Anti-Microbial (Optional)
RECOMMENDED INSTALLATION	Quarter Turn or Monolithic

SPECIFICATIONS


COLOURLINE




DOMAIN - 740



DOMAIN - 741



DOMAIN - 744




DOMAIN - 749




DOMAIN - 757




DOMAIN - 759




DOMAIN - 770




DOMAIN - 773



DOMAIN - 774




DOMAIN - 778






HOW TO INSTALL

QUARTER TURN



MONOLITHIC





Standard
CARPETS

www.standardcarpets.com